**Document:** Final Rule, **Register Page Number:** 28 IR 561

Source: November 1, 2004, Indiana Register, Volume 28, Number 2

Disclaimer: This document was created from the files used to produce the official CD-ROM Indiana Register.

## TITLE 675 FIRE PREVENTION AND BUILDING SAFETY COMMISSION

LSA Document #04-8(F)

## DIGEST

Amends 675 IAC 14-4.2-30 and 675 IAC 14-4.2-89.2 concerning the Indiana Residential Code. Effective 30 days after filing with the secretary of state.

675 IAC 14-4.2-30 675 IAC 14-4.2-89.2

SECTION 1. 675 IAC 14-4.2-30 IS AMENDED TO READ AS FOLLOWS:

675 IAC 14-4.2-30 Section R316.2; guard opening limitations

Authority: IC 22-13-2-2; IC 22-13-2-13

Affected: IC 22-12; IC 22-13; IC 22-14; IC 22-15; IC 36-7

Sec. 30. Add in the first sentence of Change SECTION R316.2 decks" between to read as follows: Guard opening limitations. Required guards on open sides of stairways, raised floor areas, balconies, decks, and "and". porches shall have intermediate rails or ornamental closures which do not allow passage of a sphere 4 inches (102 mm) or more in diameter.

EXCEPTIONS: 1. The triangular openings formed by the riser, tread, and bottom rail of a guard at the open side of a stairway are permitted to be of such a size that will not allow the passage of a sphere 6 inches (152 mm) or more in diameter.

2. Openings for required guards on the sides of stairways shall not allow the passage of a sphere 4% inches (111 mm) or more in diameter.

(Fire Prevention and Building Safety Commission; 675 IAC 14-4.2-30; filed May 23, 2001, 4:02 p.m.: 24 IR 3042; filed Sep 30, 2004, 10:00 a.m.: 28 IR 562)

SECTION 2. 675 IAC 14-4.2-89.2, AS ADDED AT 27 IR 2269, SECTION 39, IS AMENDED TO READ AS FOLLOWS:

## 675 IAC 14-4.2-89.2 Table R703.4; weather-resistant siding attachment and minimum thickness

Authority: IC 22-13-2-2; IC 22-13-2-13

Affected: IC 22-12; IC 22-13; IC 22-14; IC 22-15; IC 36-7

Sec. 89.2. Change TABLE R703.4 as follows:

- 1. In the column titled "Sheathing paper required", change "NO" to "YES" at all three (3) places for Horizontal Aluminum; change the "No" to "Yes" for Vinyl Siding and change (13) to (m) for Brick Veneer, Concrete Masonry veneer.
- 2. Change footnote m to read as follows: For masonry veneer, a weather-resistant sheathing paper is not required over water-repellent sheathing materials applied according to manufacturer's instructions and a three-fourths ¾ inch (nineteen (19 millimeter) air space is provided. When the three-fourths ¾ inch (nineteen (19 millimeter) space is filled with mortar, a weather-resistant sheathing paper is required over the sheathing.
- 3. In the column titled "Sheathing paper required", add a footnote designation "s" at all three (3) places for Horizontal Aluminum and for Vinyl Siding.
- 4. Add a new footnote "s" to read as follows: For horizontal aluminum and vinyl siding, a weather-resistant sheathing paper is not Unless required over water-repellent sheathing materials applied according to by the siding manufacturer's instruction. installation instructions.

(Fire Prevention and Building Safety Commission; 675 IAC 14-4.2-89.2; filed Feb 23, 2004, 8:34 a.m.: 27 IR 2269; filed Sep 30, 2004, 10:00 a.m.: 28 IR 562)

LSA Document #04-8(F)

Notice of Intent Published: February 1, 2004; 27 IR 1616 Proposed Rule Published: April 1, 2004; 27 IR 2333 Hearing Held: June 16, 2004; August 3, 2004 Approved by Attorney General: September 23, 2004

Approved by Governor: September 27, 2004

Filed with Secretary of State: September 30, 2004, 10:00 a.m.

IC 4-22-7-5(c) notice from Secretary of State regarding documents incorporated by reference: None received by Publisher